
EcoTank L6570



DATASHEET / BROCHURE



This ultra-fast, high-capacity multifunction EcoTank delivers a low cost per page with minimal itervention to save you time and money.

Print, scan, copy and fax will this easy-to-use EcoTank printer, that delivers an exceptionally low cost per page. Tasks can be accomplished quickly thanks to fast print and scan speeds, two 250-sheet front trays, a 50-sheet rear feed, and a 50-sheet ADF. Print how you like with mobile printing, Ethernet and a 10.9cm LCD touchscreen.

Get more done in less time

Get the edge with this fast and efficient printer that can deliver a first page in as little as 5½ seconds¹ and print speeds of 25ppm in both black and colour². Coupled with fast double-sided printing, and a high speed Automatic Document Feeder, you'll be able to speed through everyday tasks.

Feature-rich A4 EcoTank

The L6570 is designed for business with print, scan, copy and fax. Selecting features is easy with the LCD touchscreen.

Keep on saving

Save every time you print with this EcoTank that delivers an incredibly low cost per page. Unlike other printers, EcoTank features large ink tanks that you fill with low-cost ink bottles.

End interuptions

Minimising refills, this EcoTank can print thousands of pages before needing more ink, while the two 250 sheet front loanding paper trays and a generous 50-sheet rear feed offer a capacity of 550-sheets.

Print from almost anywhere

It's easy to print from mobiles, tablets and laptops using EcoTank. With Wi-Fi and Wi-Fi Direct, you can send documents to print from smart devices using the Epson iPrint³ app.

Easy to use and reliable

Filling the large front ink tanks is simple with the resealable, intuitive and drip-free ink bottles. This printer uses the heat-free PrecisionCore printhead, that's renowned for its speed, quality, reliability and efficiency, and will last the lifetime of the printer.

KEY FEATURES

- Ultra-fast print and scan speeds 25ppm in black and color²
- Ultra-low-cost per page Economical ink tank system
- Easy to use front ink tank Enjoy hassle and mess-free refills with enhanced ink bottles
- Mobile printing and connectivity Wi-Fi, Wi-Fi Direct, Ethernet & free mobile printing apps³
- Designed for business 2x A4 250-sheet front tray, 50-sheet rear feed, 50-sheet A4 ADF



PRODUCT SPECIFICATIONS

TECHNOLOGY				
Printing Method	PrecisionCore [™] Print Head			
Minimum Droplet Size	3.8 pl Pigment ink			
Ink Technology				
Printing Resolution	4,800 x 2,400 DPI			
PRINT				
	34 25 pages/min Monochrome, 25 pages/min Colour			
Maximum Printing Speed	32 pages/min Monochrome (plain paper 75 g/m²), 32 pages/min Colour (plain paper 75 g/m²)			
Colours	Black, Cyan, Yellow, Magenta			
For detailed information on printing speeds please visit http://www.epson.eu/testing.				
SCAN				
Optical Resolution	1,200 DPI x 2,400 DPI (Horizontal x Vertical)			
Scanner type	Contact image sensor (CIS)			
FAX	200 names and numbers			
Fax speed dials (max) Page memory	200 names and numbers Up to 550 pages/ 6MB (ITU-T No. 1 chart)			
Fage memory Fax Functions	PC Fax, Fax to E-mail, Memory Reception, Auto Redial, Address Book, Broadcast Fax, Fax			
	Preview, Polling Reception			
	rieview, rolling heception			
PAPER / MEDIA HANDLING	i			
Number of paper trays	3			
Paper Formats	A4 (21.0x29.7 cm), A5 (14.8x21.0 cm), A6 (10.5x14.8 cm), B6, B5, No. 10 (Envelope), DL			
	(Envelope), C6 (Envelope), C4 (Envelope), Letter, Legal			
Duplex	Yes (A4, plain paper)			
Automatic Document Feed	50 pages			
Paper Tray Capacity	550 Sheets Standard			
Media Handling	ADF 2-sided copy (A4, plain paper), ADF 2-sided fax (A4, plain paper), ADF 2-sided scan (A4			
	plain paper), Automatic duplex (A4, plain paper), Borderless Print			
GENERAL				
Energy Use	19 Watt (standalone copying, ISO/IEC 24712 pattern), 0.8 Watt (sleep mode), 9.1 Watt (Ready			
	0.2 Watt (Power off), TEC 0.14 kWh/week			
Product dimensions	425 x 500 x 350 mm (Width x Depth x Height)			
Product weight	17.8 kg			
Compatible Operating	Mac OS X 10.6.8 or later, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 b			
Systems	Windows 8.1 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 R2, Windows Server			
	2016, Windows Vista (32/64 bit), Windows XP Professional x64 Edition SP2 or later, Windows			
	XP SP3 or later (32-bit), Windows Server 2003 R2, Windows Server 2003 SP2 or later, XP			
	Professional x64 Edition			

LOGISTICS INFORMATION

SKU	C11CJ29403 C11CJ29403DA	
EAN code	8715946676449	
Country of Origin	Philippines	
Layer	2 Units	

EcoTank L6570

WHAT'S IN THE BOX

- Power cable
- Main unit

Quick Start Guide

- User guide
- 1 set of ink (1x 127ml BK, 3x 70ml cmY)

INK BOTTLE COMPATIBILITY

112	
112	EPSON 112
112	
112	

INK BOTTLE YIELD DATA

Electric Biological Bi	●	•••	
ncluded	4,500	2,800	

Included	4,500 pages*	2,800 pages*
Replacement	7,500 pages*	6,000 pages*

* Approx. page yield based on ISO/IEC 24711/24712 or ISO/ IEC 29102/29103. Actual yield will vary depending on images printed and usage conditions. For more information visit http://www.epson.eu/pageyield

* Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04

(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742

Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway +47 67 11 37 00 Poland 0-0-800 4911299 (0,16 zł/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711)

465-9621 Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal – 0,99 kr/min, Lokala samtal – 0,30 kr/min, Utlandssamtal – 0,89 kr/min) Switzerland 022 592 7923

Turkey (0212) 3360303 United Kingdom 0871 222 6702

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice. 1. Determined in accordance with ISO/IEC 17629 showing the average of FPOT(sec) from the Office Category Test for default A4 simplex. For more information, please visit

www.epson.eu/testing 2. Determined in accordance with ISO/IEC 24734 showing the average of ESAT from the Office Category Test for default simplex. For more information visit

www.epson.eu/testing

3. Requires a wireless connection to the internet. For more information, supported languages and devices please visit www.epsonconnect.eu

